

# HomeGard Interior

100% Special Acrylic Emulsion Paint for Interior

## DESCRIPTION

HomeGard Interior is a specially formulated for interior use on wall and ceiling surfaces. Its matt finish makes it ideal for minimizing surface imperfections and is ideally used where side sheen is undesirable. It is quick-drying paint of high viscosity with easy application, good flow and superior hiding power characteristics and resistant to fungal growth.

## RECOMMENDED USE

Suitable for use on cement, masonry, fiber cement and previously painted surfaces. For interior use only.

## TECHNICAL INFORMATION & PAINT FILM PROPERTIES

- |                        |   |
|------------------------|---|
| • Type of paint        | : 100% Special Acrylic  |
| • Finish               | : Matt  |
| • Color                | : Refer to the appropriate Dimet color card                                     |
| • Drying Time          | (Environment condition)   |
| Touch Dry              | : 20-30 minutes   |
| Recoat                 | : 2 hours   |
| • Theoretical coverage | : 35-40 sq.m./ US. Gallon   |
| • Wet film thickness   | : 80-95 microns (wet)   |
| • Dry film thickness   | : 30-35 microns (dry)   |
| • Packaging            | : 1 US. Gallon and 5 US. Gallon   |
| • Shelf Life           | : Up to 12 months provided it is kept in a tightly sealed container below 35° C |
| • Application Method   | : Roller, Brush or Spray  |
| • Thinner              | : No more 10% of clean water dilutions.   |
| • Cleaner              | : Water   |

## APPLICATION SYSTEM

### Surface Preparation

- |                                       |  |
|---------------------------------------|--|
| - For new & good condition surface    | Leave surface dry for at least 1 month. Surface must be dry, clean and free from dirt and loose materials. Repair all cracks with a suitable stopping compound.  |
| - For old, powdery or friable surface | All loose, peeling and flaking material must be removed. After identifying the presence of mould, mildew or fungi, it is necessary to remove the growth then sterilize the surfaces before repainting. |

### Primer

- |                                       |  |
|---------------------------------------|--|
| - For new & good condition surface    | Apply 1-2 coats of HomeGard Primer. Allow at least 2 hours drying before apply top coat.               |
| - For old, powdery or friable surface | Apply 1-2 coats of HomeGard Sealer Solvent Based. Allow at least 2 hours drying before apply top coat. |

### Coating

Apply 2 coats of HomeGard Interior. Allow 2-3 hours drying between coats.

## HEALTH AND SAFETY

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

## DISCLAIMER

The information in this datasheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.