

DIMET DECKING STAIN SEMI TRANSPARENT

Exterior Floor Coating

DESCRIPTION

- Dimet Decking Stain Semi Transparent is urethane modify specially formulated to provide a tough protective and attractive surface finish to exterior flooring. This unique formulation contains an effective ultra-violet absorber to counter the destructive effects of the sun's rays which can darken and discolour exterior woodwork.

INSTRUCTIONS FOR USE

- Dimet Decking Stain Semi Transparent is high build and easy to use. Generally recommended to be applied with 3 coats system. It is suitable for maintenance areas such as exterior floor, doors, windows, timber paneling, railings, weatherboards, exposed beams and other locations.
- It is recommended to apply test this product to determine if it is suitable for your particular use.

BASIC DATA AT 25°C and 50% RELATIVE HUMIDITY

- | | |
|------------------------|---|
| • Type of paint | Alkyd |
| • Finish | Matt, Semi Gloss, Gloss |
| • Colour | Clear |
| • Theoretical coverage | 80 sq.m./US.Gallon/Coat |
| • Wet film thickness | 40 microns |
| • Dry film thickness | 20 microns |
| • Thinner | Thinner T21 |
| • Cleaner | Thinner T21 |
| • Apply by | Brush or Spray |
| • Drying Time | Under normal temperature and humidity conditions |
| • Tack free | 4 hours |
| • Recoat | it can be lightly sanded and recoated after a minimum of 24 hours air drying. |
| • Packaging | 1/4 US.Gallon and 1 US.Gallon |
| • Shelf Life | Up to 12 months provided it is kept in a tightly sealed container below 35° C |

DIMET DECKING STAIN SEMI TRANSPARENT

Exterior Floor Coating

SURFACE PREPARATION

- Ensure that the timber is dry and free from dirt, wax, grease and oil. If necessary, wash the surface using a household detergent, rinse and allow to dry.
- After identifying the presence of mould, mildew or fungi, it is necessary to remove the growth then sterilize the surface before repainting.

New Timber : Sand if necessary and remove dust.

Previously Stained Timber-Good Condition

: Spot prime any bare patched with Dimet Decking Stain Semi Transparent in the matching colour and allow to dry before coating the entire area.

Coating : Apply 2-3 coats of Dimet Decking Stain Semi Transparent. Lightly sand between coats.

Note

- Apply one coat to correctly prepared surface by brush or spray equipment.
- A second coat will produce a good protection and will be more opaque.
- The moisture content of the substrate should be low as high moisture content in the substrate is the common cause for premature paint failure.

SAFETY PRECAUTIONS

- **Cautions** : Flammable. Provide adequate ventilation during use.
: The durability of this product depends entirely on film build. Three coats is an absolute minimum.
: Proper maintenance is essential with this product. Check the coated surface at least twice a year. Lightly sand out cracks or discoloured areas and recoat as required.
- For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Ensure adequate ventilation during use.

DISCLAIMER

- The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.